

屋内照明器具特性

品番 (品名)	NNN1 1 2 6 0									
光源	LDA5 L - D - G - E17 / S / Z4 ×1 440.0 1 m									
管理番号	K0172977 (0) DR 1									
BZ分類	BZ6									

器具効率	85 %	天井	80 %				70 %				50 %				30 %				0 %																																	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																																	
		床	10 %				10 %				10 %				10 %				0 %																																	
上方光束	42 %	室指数																	照明率 (X0.01)																	ZCM																
下方光束	43 %																																																			
保守率	良 中 否 0.63 0.6 0.56	0.6	41	31	25	20	38	29	23	19	32	25	20	17	26	21	17	14	10																																	
		0.8	48	39	32	28	45	36	30	26	37	31	26	23	31	26	22	20	14																																	
		1.0	54	45	38	33	49	41	36	31	41	35	31	27	34	30	26	23	17																																	
		1.25	58	50	44	39	54	46	41	37	45	40	35	32	37	33	30	27	20																																	
下方投影面積	c m ²	1.5	62	54	48	43	57	50	45	41	48	43	39	35	40	36	33	30	22																																	
		2.0	66	60	54	50	61	55	51	47	51	47	44	40	43	40	37	34	25																																	
取付高さ	器具間隔最大限		2.5	69	63	58	54	64	59	55	51	54	50	47	44	45	42	40	37	27																																
	横方向 (A)	縦方向 (B)	3.0	71	66	62	58	66	61	57	54	56	52	49	47	46	44	42	40	29																																
H m	1.56 H m	1.72 H m	4.0	73	69	66	63	68	65	61	58	58	55	53	50	48	46	44	43	31																																
			5.0	75	72	69	66	70	67	64	61	59	57	55	53	50	48	46	45	33																																
			7.0	77	74	72	70	72	69	67	65	61	59	58	56	51	50	49	47	35																																
			10.0	79	77	75	73	73	71	70	68	63	61	60	59	53	52	51	50	36																																

