

屋内照明器具特性	
品番 (品名)	NNN12230
光源	LDA5L-D-G-E17/S/Z4 ×1 440.0 l m
管理番号	K0172978(0)DR1
BZ分類	BZ8

器具効率	59%	反射率	天井	80%				70%				50%				30%				0%
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	25%	床	10%				10%				10%				10%				0%	
下方光束	34%	室指数	照明率 (X0.01)																ZCM	
保守率	良 0.63	0.6	2.7	1.9	1.4	1.1	2.5	1.8	1.3	1.0	2.1	1.5	1.2	9	1.7	1.3	1.0	8	5	
	中 0.6	0.8	3.2	2.4	1.9	1.6	2.9	2.2	1.8	1.5	2.4	1.9	1.5	1.3	2.0	1.6	1.3	1.1	7	
	否 0.56	1.0	3.5	2.8	2.3	1.9	3.2	2.6	2.1	1.8	2.7	2.2	1.8	1.5	2.3	1.9	1.6	1.3	9	
		1.25	3.8	3.2	2.7	2.3	3.5	2.9	2.5	2.1	3.0	2.5	2.1	1.9	2.5	2.1	1.8	1.6	1.1	
下方投影面積	cm ²	1.5	4.1	3.4	3.0	2.6	3.8	3.2	2.8	2.4	3.2	2.7	2.4	2.1	2.7	2.3	2.0	1.8	1.3	
等価発光面積	cm ²	2.0	4.4	3.9	3.4	3.0	4.1	3.6	3.2	2.9	3.5	3.1	2.8	2.5	2.9	2.6	2.3	2.1	1.5	
取付高さ	器具間隔最大限		2.5	4.6	4.1	3.7	3.4	4.3	3.9	3.5	3.2	3.7	3.3	3.0	2.8	3.1	2.8	2.6	2.4	1.7
	横方向 (A)	縦方向 (B)	3.0	4.8	4.3	4.0	3.6	4.4	4.1	3.7	3.4	3.8	3.5	3.2	3.0	3.2	3.0	2.8	2.6	1.9
Hm	1.53Hm	1.71Hm	4.0	5.0	4.6	4.3	4.0	4.6	4.3	4.0	3.8	4.0	3.7	3.5	3.3	3.4	3.2	3.0	2.8	2.1
			5.0	5.1	4.8	4.5	4.3	4.8	4.5	4.3	4.0	4.1	3.9	3.7	3.5	3.5	3.3	3.2	3.0	2.3
			7.0	5.3	5.0	4.8	4.6	4.9	4.7	4.5	4.3	4.3	4.1	3.9	3.8	3.7	3.5	3.4	3.3	2.5
			10.0	5.4	5.2	5.1	4.9	5.1	4.9	4.8	4.6	4.4	4.3	4.2	4.0	3.8	3.7	3.6	3.5	2.7

