

屋内照明器具特性

品番 (品名)	LGB81770										
光源	LED5000_70_2500 x1 2500.0 1m										
管理番号	K0161531(0)DR1										
BZ分類	BZ9/0.7/BZ8										

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	50%	床	10%				10%				10%				10%				0%	
下方光束	50%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.63	0.6	45	33	25	19	41	30	23	18	34	25	19	15	27	20	16	12	7
	中	0.6	0.8	53	41	33	27	49	38	31	25	40	32	26	21	32	26	21	17	11
	否	0.56	1.0	59	48	39	33	54	44	36	31	45	37	31	26	36	30	25	21	13
			1.25	65	54	46	39	59	50	42	37	49	42	36	31	40	34	29	26	17
下方投影面積		cm ²	1.5	69	59	51	45	63	54	47	41	52	45	40	35	42	37	33	29	19
等価発光面積		cm ²	2.0	75	66	59	53	68	61	54	49	57	51	46	42	46	42	38	34	23
取付高さ	器具間隔最大限		2.5	78	70	64	58	72	65	59	54	60	55	50	46	49	45	41	38	26
	横方向 (A)	縦方向 (B)	3.0	81	74	68	63	74	68	63	58	62	58	53	50	51	48	44	41	28
1.5m	2.44m	2.16m	4.0	84	78	73	69	78	73	68	64	66	62	58	55	54	51	48	46	32
2	3.22	2.72	5.0	86	82	77	73	80	76	72	68	68	64	61	58	56	53	51	49	34
2.5	4	3.3	7.0	89	85	82	78	83	79	76	73	70	67	65	62	58	56	54	52	37
3	4.79	3.88	10.0	91	88	86	83	85	82	80	77	72	70	68	66	60	59	57	56	40

