

屋内照明器具特性

品番 (品名)	NNY20246K														
光源	LED2700_70_1490 x1 1490.0 lm														
管理番号	K0167903(0)DR1														
BZ分類	BZ9														

器具効率	100%	天井	80%				70%				50%				30%				0%																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																				
		床	10%				10%				10%				10%				0%																																				
上方光束	50%	室指数																		照明率 (X0.01)																		ZCM																	
下方光束	50%																																																						
保守率	良 中 否 0.63 0.6 0.56	0.6	44	32	24	18	40	29	22	17	33	24	18	14	26	19	15	11	6																																				
		0.8	52	40	32	25	48	37	29	23	39	30	24	20	31	25	20	16	9																																				
		1.0	58	46	38	31	53	42	35	29	44	35	29	24	35	28	23	19	11																																				
		1.25	64	52	44	37	58	48	41	35	48	40	34	29	38	32	27	24	14																																				
下方投影面積	c m ²	1.5	68	57	49	42	62	53	45	39	51	44	38	33	41	35	31	27	17																																				
		2.0	73	64	56	50	67	59	52	46	56	49	44	39	45	40	36	32	21																																				
取付高さ	器具間隔最大限		2.5	77	69	62	56	71	63	57	52	59	53	48	44	48	43	39	24																																				
	横方向 (A)	縦方向 (B)	3.0	80	72	66	60	73	67	61	56	61	56	51	47	50	46	42	26																																				
H m	1.38 H m	1.53 H m	4.0	83	77	72	67	77	71	66	62	64	60	56	52	53	49	46	29																																				
			5.0	86	80	75	71	79	74	70	66	66	63	59	56	55	52	49	32																																				
			7.0	88	84	80	77	82	78	74	71	69	66	63	61	57	55	53	35																																				
			10.0	91	87	84	81	84	81	78	76	71	69	67	65	59	58	56	38																																				

