

屋内照明器具特性

品番 (品名)	XNW2060WN	
光源	LED5000_85_1950 ×1	1950.0lm
管理番号	K0164306(0)DB1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%				
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%				
上方光束	0%	反射率	壁	10%				10%				10%				10%				0%			
下方光束	100%		床	10%				10%				10%				10%				0%			
		室指数	照明率 (X0.01)																ZCM				
保守率	良	0.81	0.6	87	82	78	76	86	82	78	76	85	81	78	76	84	80	78	76	75			
	中	0.77	0.8	92	88	84	82	92	87	84	82	90	86	84	82	89	86	83	81	80			
	否	0.68	1.0	96	91	88	86	95	91	88	86	93	90	87	85	92	89	87	85	84			
下方投影面積	cm ²	等価発光面積	cm ²	1.25	98	94	92	89	97	94	91	89	96	93	90	89	94	92	90	88	87		
				1.5	100	96	94	92	99	96	93	92	97	95	93	91	96	93	92	90	89		
取付高さ	器具間隔最大限		Hm	0.81Hm	0.81Hm	2.5	103	101	99	97	102	100	98	97	100	99	97	96	99	97	96	95	93
	横方向 (A)	縦方向 (B)				3.0	104	102	100	99	103	101	100	98	101	100	98	97	99	98	97	96	94
Hm	0.81Hm	0.81Hm	4.0	105	104	102	101	104	103	101	100	102	101	100	99	100	99	98	98	95			
			5.0	106	105	103	102	105	104	103	102	103	102	101	100	101	100	99	99	96			
			7.0	107	106	105	104	105	105	104	103	103	103	102	101	101	101	100	100	97			
			10.0	107	106	106	105	106	105	105	104	104	103	103	102	102	101	101	101	98			

